

## 4G630

Easily share your mobile broadband virtually anywhere

### 3G/4G Wireless N300 Router

The Tenda 4G630 3G/4G Wireless N300 Router is designed for wireless network deployment in remote location or temporary command centers. The device provides 3G/4G wireless WAN and wired Ethernet connectivity to keep you connected with your family, friends or colleagues. By simply plug a compatible 3G/4G USB modem, a secure, wireless speeds of up to 300Mbps wireless network is created to share by multiple users. Use 3G/4G as primary connection while wired connection as backup, the device automatically failover to wired connection when 3G/4G signal is lost, and failback when it resumes. In addition, the universal repeater functionality enables the 4G630 to connect to an existing WiFi and create secure connections.



### Smart Connection

Automatically connect to a cellular network and create a high speed WiFi hotspot to share by multiple users when a compatible 3G/4G USB modem is plugged



### 300Mbps wireless speed

4G630 3G/4G signal can be converted to 300Mbps wireless signal, which can meet the phone, ipad, laptop, etc. 10-12 terminals simultaneously access and provide high-speed data transmission



### Always Connected

Engineered for 24/7 Internet connectivity, automatic failover to the wired connection when 3G/4G mobile connection is disrupted



### High Compatibility

Plug-and-play supports for over 300 of the most popular LTE-FDD/ LTE-TD/HSPA+/HSPA/EVDO USB modems

## Specifications

Hardware Specs	
Standard	IEEE 802.11n、 IEEE 802.11g、 IEEE 802.11b ; IEEE 802.3、 IEEE 802.3u
Interface	3 10/100M adaptive LAN ports (Auto MDI/MDIX); 1 10/100M adaptive WAN port (Auto MDI/MDIX); 1 USB 2.0 interface
Antenna	Two fixed 5dBi Omni Directional antennas
Button	1*WPS/RESET
Power	Input Voltage Range(VAC): AC 110-240V Output Voltage(VDC): DC 9V 600mA
Dimensions ( L*W*H )	171.55mm*110mm*25.3mm
Indicator	Power: Often bright, indicates normal power supply WPS: Flashing, Indicates link building SYS: Flashing, Indicates normal operating system USB: Often bright, indicates normal linkage 1*WLAN: Flashing, indicates normal wireless signal 3*WAN: Flashing, indicates data receiving and trasfering LAN: Ofen bright; normal linkage, flashing, indicates data receiving or transferring
Wireless Features	
Wireless Link Rate	300Mbps
Frequency Range	2.4-2.4835GHz
Basic Function	Client Filter SSID,Broadcast Channel
Wireless Security	WPA-PSK/WPA2-PSK WPA/WPA2 WEP
Software Features	
Internet Connection Type	3G/4G, PPPOE DHCP Static IP PPTP L2TP
Working Mode	wireless router 3G/4G Router Universal Reapter
DHCP	DHCP Server DHCP Client List DHCP Reservation
VPN Pass-Through	ipsec VPN PPTP L2TP
Others Advanced Function	UPNP DDNS Smart Switch, Circuit Backup

Others	
Temperature	Operating Temperature: 0°C~40°C Storage Temperature: -30°C~70°C
Humidity	Operating Humidity: 10% ~ 90% RH Non-condensing Storage Humidity: 5% ~ 90% RH Non-condensing
Factory Default Settings	Login IP Address: 192.168.0.1 Login User Name/Password: admin/admin SSID: Tenda_xxxxxx (where "xxxxxx" represents the last six characters of device MAC address) Internet Connection Type: DHCP
Certificates	FCC CE RoHS
Related Products	4G600 4G631
Package Contents	4G630 Power Adapter Quick Install Guide Resource CD

## SHENZHEN TENDA TECHNOLOGY CO.,LTD.

No. 34-1 Shilong Road Shiyan Town, Baoan District Shenzhen 518108,China

Phone: (86 755) 2765 7180 Fax:(86 755) 2765 7178

Email: sales@tenda.com.cn support@tenda.com.cn

<http://www.tendacn.com>



© 2013 SHENZHEN TENDA TECHNOLOGY CO.,Ltd, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.