

AH302

Boost Wireless Coverage to Eliminate 'Dead Zone' in Your Home Network

Wireless N300 High Power Universal Range Extender

The AH302 Wireless N300 High Power Universal Range Extender is specifically designed to expand the range of your 802.11b/g/n wireless network by repeating the signal from your home or office wireless router. The extender eliminates wireless dead zones, giving you the freedom to roam anywhere in the house or office and access Internet without worrying about coverage. It is compatible with all brands of wireless b/g/n routers. In addition, it provides four Ethernet ports for you to connect wired devices like Blu-ray players, gaming consoles, DVRs, and Internet TVs.



High Powered Design

High Power Amplifiers and 2x5dBi Antennas provide powerful Wi-Fi coverage that easily penetrates walls and Wi-Fi obstructions to eliminate hard to reach wireless dead spots.



Push & Connect

Easily extend the range of the current wireless network to enjoy increased in-home mobility at a push of Extender button.



Extended Wireless Coverage

Boost the range of your existing home or office wireless network to a greater distance by repeating the existing Wi-Fi signal

Specifications

Wireless Standards	802.11n/g/b, IEEE 802.3/802.3u
Interface	4*10/100M LAN
Antenna	2* 5 dBi external antenna
Button	Range Extender button reset button
Power Supply	Input: 100-240V~50/60Hz 0.3A Output: DC 9V==1A
Product Dimensions (L*W*H)	172mm*111mm*25mm
LEDs	1* Power, 1* RE(Range Extender), 3*signal strength LEDs (Strong, medium, weak), 4*LAN LEDs
Wireless Rate	Up to 300Mbps
Frequency	2.412GHz-2.472GHz
Wireless Functions	Wi-Fi Switch; SSID broadcast switch; Adjustable TX power: high, medium, low; Domain Login Function.
Wireless Security	Wireless Access Control; Wireless security switch; 64/128-bit WEP; WPA-PSK/WPA2-PSK, WPA-PSK, WPA2-PSK.
Wireless Mode	Range Extender mode (Universal Repeter), AP mode
DHCP Settings	DHCP Server; DHCP Client List;
Temperature	Operating Temperature: 0℃~40℃ Storage Temperature: -40℃~70℃
Humidity	Operating Temperature: 0℃~40℃ Storage Temperature: -40℃~70℃
Default Settings	Default Access : http://tendaextender.net Login Password: admin
Certification	CE; FCC; RoHS
Related Products	D301 Wireless N300 ADSL2+ Modem Router D302 Wireless N300 ADSL2+ Modem Router F300 Wireless N300 Router
Package Contents	Wireless N300 High Power Universal Range Extender Power Adapter Ethernet cable Quick Installation Guide Resources CD

SHENZHEN TENDA TECHNOLOGY CO.,LTD.

No. 34-1 Shilong Road Shiyan Town, Baoan District Shenzhen 518108,China
 Phone: (86 755) 2765 7180 Fax:(86 755) 2765 7178
 Email: sales@tenda.com.cn support@tenda.com.cn
<http://www.tendacn.com>



© 2013 SHENZHEN TENDA TECHNOLOGY CO.,Ltd, the Tenda logo is registered trademark of Shenzhen Tenda Technology Co.,Ltd in China and/or other countries. Other brand and product names are trademarks or registered trademarks of their respective holders. Information is subject to change without notice. ALL rights reserved.